



Heavy Duty Reliable
Shrink System

ONE-STEP SHRINK SYSTEM



COMPACK 5800i

Characteristics

- Packaging solutions for small or medium volume of production
- One Step Shrink System. Shrinks and seals simultaneously
- Menu driven Digital Display
- No need for a heat tunnel
- Height adjustments for different heights of the products
- Practical real placement and easy to slide film housing device
- Adjustable production loading tray
- Film separator plate to open the ceter-folded film
- High output yield with low energy consumption
- Film perforator for optimal product appearance
- Shrink temperature adjustment
- Standard legs, with casters to easy mobility
- Only one operator required
- Magnetic holder for hood with time control

Technical Data

- Speed 8 to 10 Packs per minute
- Seal Bar Dimensions:
18" W x 22" L
- CE Approved
- Maximum package height 10"
- Maximum Film Roll Width 22"

Electrical Requirements

220V, 15 Amps, 1PH

Dimensions

53" L x 34" W x 52" H

Crated: 75" L x 39" W x 45" H

Weight

257 lbs. Net. 338 lbs. Crated

Authorized Distributor

STRATEGICGROUP
PACK FASTER. PACK SMARTER

254 W. Airport Frwy. Irving, TX 75062
Tel: 972-438-2995 • Fax: 972-438-2876
www.sgroup.org • info@sgroup.org